












# GHKE Castors with SAS Series Polyurethane Wheels

Muvtons Premium Polyurethane treaded wheels  $93^{\circ} \pm 3^{\circ}$  Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running, are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range :  $-20^{\circ} \text{C}$  to  $+85^{\circ} \text{C}$ . Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GHKE-8575S-SAS	GHKE-8575S-SAS-TL	GHKE-8575R-SAS	85 x 75	133	100	93	138 x 110	105 x 75-80	10	650
GHKE-42S-SAS	GHKE-42S-SAS-TL	GHKE-42R-SAS	100 x 50	140	77	90				400
GHKE-52S-SAS	GHKE-52S-SAS-TL	GHKE-52R-SAS	125 x 50	165	95	110				550
GHKE-62S-SAS	GHKE-62S-SAS-TL	GHKE-62R-SAS	150 x 50	195	115	140				750
GHKE-82S-SAS	GHKE-82S-SAS-TL	GHKE-82R-SAS	200 x 50	245	152	163				900
GHKE-102S-SAS	GHKE-102S-SAS-TL	GHKE-102R-SAS	250 x 50	295	190	197				900