











DABE75 Forged Twin Wheel Castors with MCNY Series Cast Polyamide Wheels

Muvtons MCNY Wheels produced from high impact resistant cast polyamide are the ultimate choice for extremely high loads where metallic wheels are not an option. These wheels possess very high abrasion resistance and offer low rolling resistance under extreme loads. Can be used in corrosive applications. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or plain bore. Temperature range : -30° C to +80° C.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABE75-84S-MCNY	DABE75-84S-MCNY-WFB	DABE75-84R-MCNY	200 x 100 x 2	280	200	350	255 x 200	210 x 160	16	7500
DABE75-104S-MCNY	DABE75-104S-MCNY-WFB	DABE75-104R-MCNY	250 x 100 x 2	330	226	375				7500
DABE75-124S-MCNY	DABE75-124S-MCNY-WFB	DABE75-124R-MCNY	300 x 100 x 2	395	261	420				7500