












DABE50 Forged Twin Wheel Castors with SEB Series Elastic Rubber Tyred Wheels

Muvtons - black Elastic Rubber tyred wheels firmly chemically bonded to precision machined cast iron cores. Highly resilient $75^{\circ} \pm 5^{\circ}$ Shore A rubber provides very smooth and silent running. Can be used for power towing applications by suitably de-rating the load capacity. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20°C to $+75^{\circ} \text{C}$. Tread Options : Anti-static; conductive and oil resistant wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centres (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABE50-63S-SEB	DABE50-63S-SEB-WFB	DABE50-63R-SEB	150 x 75 x 2	212	160	310	200 x 160	160 x 120	16	850
DABE50-83S-SEB	DABE50-83S-SEB-WFB	DABE50-83R-SEB	200 x 75 x 2	264	190	350				1100
DABE50-103S-SEB	DABE50-103S-SEB-WFB	DABE50-103R-SEB	250 x 75 x 2	314	220	375				1500
DABE50-123S-SEB	DABE50-123S-SEB-WFB	DABE50-123R-SEB	300 x 75 x 2	375	245	395				1700
DABE50-163S-SEB	DABE50-163S-SEB-WFB	DABE50-163R-SEB	400 x 75 x 2	475	310	450				2400