

DABLP Forged Twin Wheel Castors with SAS Series Polyurethane Wheels

Muvtons Premium Polyurethane treaded wheels $93^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running, are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range : -20° C to $+85^{\circ}$ C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
DABLP-522S-SAS	DABLP-522S-SAS-WFB	DABLP-522R-SAS	125 x 50 x 2	185	120	245	175 x 140	140 x 105	12	1100
DABLP-622S-SAS	DABLP-622S-SAS-WFB	DABLP-622R-SAS	150 x 50 x 2	212	140	265				1500
DABLP-822S-SAS	DABLP-822S-SAS-WFB	DABLP-822R-SAS	200 x 50 x 2	264	175	303				2000
DABLP-1022S-SAS	DABLP-1022S-SAS-WFB	DABLP-1022R-SAS	250 x 50 x 2	314	212	340				2000
DABLP-1222S-SAS	DABLP-1222S-SAS-WFB	DABLP-1222R-SAS	300 x 50 x 2	365	240	368				2000