












DABLP Forged Twin Wheel Castors with ME Series Ergonomic Wheels

Muvtons Ergonomic Wheels for effortless rolling, very low push-pull efforts required to move heavy loads. Generous amount of premium Polyurethane 93° ±3° Shore A, firmly bonded, mechanically & chemically, to precision machined cores. Proven for excellent performance in most demanding applications for manual and power towing. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Softer 83° ±3° Shore A Durometer for greater tractive resistance and harder 73° ±3° Shore D polyurethane treads for extremely low rolling resistance are also offered. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABLP-522S-ME	DABLP-522S-ME-WFB	DABLP-522R-ME	125 x 50 x 2	185	120	245	175 x 140	140 x 105	12	900
DABLP-622S-ME	DABLP-622S-ME-WFB	DABLP-622R-ME	150 x 50 x 2	212	140	265				1150
DABLP-822S-ME	DABLP-822S-ME-WFB	DABLP-822R-ME	200 x 50 x 2	264	175	303				1550
DABLP-1022S-ME	DABLP-1022S-ME-WFB	DABLP-1022R-ME	250 x 50 x 2	314	212	340				1700
DABLP-1222S-ME	DABLP-1222S-ME-WFB	DABLP-1222R-ME	300 x 50 x 2	365	240	368				2000