



GRDE Castors with SZS Series Soft Polyurethane Wheels

Muvtons Premium Soft Durometer Polyurethane treaded wheels $83^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores. These wheels have been designed in response to noise problems and allow loads to be cushioned. The use of 'lively' polyurethane materials allows these wheels to 'flex & roll' over debris and obstacles without picking up objects. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20°C to $+85^{\circ} \text{C}$. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GRDE-42S-SZS	GRDE-42S-SZS-TL	GRDE-42R-SZS	100 x 50	150	95	98	150 x 110	105 x 80	12	250
GRDE-52S-SZS	GRDE-52S-SZS-TL	GRDE-52R-SZS	125 x 50	177	115	115				350
GRDE-62S-SZS	GRDE-62S-SZS-TL	GRDE-62R-SZS	150 x 50	200	130	135				450
GRDE-82S-SZS	GRDE-82S-SZS-TL	GRDE-82R-SZS	200 x 50	250	163	162				650
GRDE-102S-SZS	GRDE-102S-SZS-TL	GRDE-102R-SZS	250 x 50	300	197	195				750