












# GHKE Castors with MCI Series Cast Iron Wheels

Muvtons special grey cast iron wheels - solid core construction, tread face fully machined and crown treaded for extremely easy maneuverability. These wheels offer high abrasion and oil resistance, can be used upto 600° C with appropriate wheel bearings. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -100° C to +600° C.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GHKE-42S-MCI	GHKE-42S-MCI-TL	GHKE-42R-MCI	100 x 50	140	77	90	138 x 110	105 x 75-80	10	450
GHKE-52S-MCI	GHKE-52S-MCI-TL	GHKE-52R-MCI	125 x 50	165	95	110				550
GHKE-62S-MCI	GHKE-62S-MCI-TL	GHKE-62R-MCI	150 x 50	195	115	140				800
GHKE-82S-MCI	GHKE-82S-MCI-TL	GHKE-82R-MCI	200 x 50	245	152	163				900
GHKE-102S-MCI	GHKE-102S-MCI-TL	GHKE-102R-MCI	250 x 50	295	190	197				900