

DABLP Forged Twin Wheel Castors with SZS Series Soft Polyurethane Wheels

Muvtons Premium Soft Durometer Polyurethane treaded wheels 83° ±3° Shore A, firmly bonded to precision machined cast iron cores. These wheels have been designed in response to noise problems and allow loads to be cushioned. The use of 'lively' polyurethane materials allows these wheels to 'flex & roll' over debris and obstacles without picking up objects. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centres (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
DABLP-522S-SZS	DABLP-522S-SZS-WFB	DABLP-522R-SZS	125 x 50 x 2	185	120	245	175 x 140	140 x 105	12	700
DABLP-622S-SZS	DABLP-622S-SZS-WFB	DABLP-622R-SZS	150 x 50 x 2	212	140	265				900
DABLP-822S-SZS	DABLP-822S-SZS-WFB	DABLP-822R-SZS	200 x 50 x 2	264	175	303				1300
DABLP-1022S-SZS	DABLP-1022S-SZS-WFB	DABLP-1022R-SZS	250 x 50 x 2	314	212	340				1500
DABLP-1222S-SZS	DABLP-1222S-SZS-WFB	DABLP-1222R-SZS	300 x 50 x 2	365	240	368				1800