












DABLP Forged Twin Wheel Castors with MCI Series Cast Iron Wheels

Muvtons special grey cast iron wheels - solid core construction, tread face fully machined and crown treaded for extremely easy maneuverability. These wheels offer high abrasion and oil resistance, can be used upto 600° C with appropriate wheel bearings. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -100° C to +600° C.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABLP-522S-MCI	DABLP-522S-MCI-WFB	DABLP-522R-MCI	125 x 50 x 2	185	120	245	175 x 140	140 x 105	12	1100
DABLP-622S-MCI	DABLP-622S-MCI-WFB	DABLP-622R-MCI	150 x 50 x 2	212	140	265				1600
DABLP-822S-MCI	DABLP-822S-MCI-WFB	DABLP-822R-MCI	200 x 50 x 2	264	175	303				2000
DABLP-1022S-MCI	DABLP-1022S-MCI-WFB	DABLP-1022R-MCI	250 x 50 x 2	314	212	340				2000
DABLP-1222S-MCI	DABLP-1222S-MCI-WFB	DABLP-1222R-MCI	300 x 50 x 2	365	240	368				2000