












ABE75 Forged Precision Bearings Castors with SZS Series Soft Polyurethane Wheels

Muvtons Premium Soft Durometer Polyurethane treaded wheels 83° ±3° Shore A, firmly bonded to precision machined cast iron cores. These wheels have been designed in response to noise problems and allow loads to be cushioned. The use of 'lively' polyurethane materials allows these wheels to 'flex & roll' over debris and obstacles without picking up objects. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
ABE75-84S-SZS	ABE75-84S-SZS-WFB	ABE75-84R-SZS	200 x 100	280	165	325	255 x 200	210 x 160	16	1400
ABE75-104S-SZS	ABE75-104S-SZS-WFB	ABE75-104R-SZS	250 x 100	330	195	355				1600
ABE75-124S-SZS	ABE75-124S-SZS-WFB	ABE75-124R-SZS	300 x 100	395	235	395				2100