



BDS-615S-PNY

Fork Properties

450Kgs. Load Capacity Heavy Duty Pressed Steel Castors

- Extra heavy duty pressed steel brackets thick steel construction
- Swivel brackets with double ball bearing raceways dynamically pressed ensure low swivel head play and long service life
- Kingpinless swivel head design in larger wheel diameters eliminates chances of kingpin failure
- Finish : Zinc Plated
- Options : Total Lock Brake System

Wheel Properties

Liquid Cast Quality polyurethane chemically and mechanically to a strong polyamide core. Non-corrosive & non-marking 95° shore A, non-Staining, abrasion-resistant, floor-saving, low-noise operation, low rolling resistance tested & guaranteed against bond failures. Wheel Bearing Options: Sealed precision ball bearing or roller bearings. Temperature range:-20°C to +85°C. Alternatively available with soft polyurethane tread.

Technical Data

Castor Type	Swivel Castor without Brake
Wheel Material	Polyurethane
Wheel Hardness	95° Shore A
Wheel Center	Nylon Polyamide
Wheel Dia(mm)	150
Tread Width(mm)	40
Load Capacity(kg)	400
Wheel Bearing	Ball Bearing
Overall Height(mm)	190
Swivel Radius(mm)	130
Top Plate(mm)	135 x 110
Bolt Hole Centers	105 x 75-80
Non Marking	Yes
Heat Resistant	Yes
Noise Reduction	Yes

