











BDS Series Castors with SJS Series Polyurethane Wheels

Muvtons medium duty Polyurethane treated wheels $93^{\circ} \pm 3^{\circ}$ Shore A for medium applications offer a cost effective yet a good solution. Polyurethane tread, firmly bonded to precision machined cast iron core offers smooth & noiseless running, non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearing or roller bearings. Temperature range :- 20°C to $+85^{\circ}\text{C}$.



Part No. Swivel Castor	Part No. Swivel With Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (Kgs)
									
BDS-415S-SJS	BDS-415-SJS-TL	BDS-415R-SJS	100 x 40	128	90	105 x 85	80 x 60	8	225
BDS-515S-SJS	BDS-515-SJS-TL	BDS-515R-SJS	125 x 40	155	105				350
BDS-62S-SJS	BDS-62-SJS-TL	BDS-62R-SJS	150 x 50	190	130				450
BDS-82S-SJS	BDS-82-SJS-TL	BDS-82R-SJS	200 x 50	238	160	135 x 110	105 x 75-80	10	450
BDS-102S-SJS	BDS-102-SJS-TL	BDS-102R-SJS	250 x 50	290	180				450