



BDS-415-SJS-TL

Fork Properties

450Kgs. Load Capacity Heavy Duty Pressed Steel Castors

- Extra heavy duty pressed steel brackets thick steel construction
- Swivel brackets with double ball bearing raceways dynamically pressed ensure low swivel head play and long service life
- Kingpinless swivel head design in larger wheel diameters eliminates chances of kingpin failure
- Finish : Zinc Plated
- Options : Total Lock Brake System

Wheel Properties

Muvtons medium duty polyurethane treaded wheels 93° ±3c shore a for medium and light applications offer a cost effective yet a good solution polyurethane treads is firmly bonded to precision machined and floor protective. Tested & guaranteed against bond failures. Wheel bearing options: sealed precision ball bearings, tapered roller bearings or roller bearings. Color: light brown, temperature range : -20 °c to +85 °c.

Technical Data

Castor Type	Swivel Castor with Brake
Wheel Material	Polyurethane
Wheel Hardness	93° ± 3° Shore A
Wheel Center	Cast Iron
Wheel Dia(mm)	100
Tread Width(mm)	40
Load Capacity(kg)	225
Wheel Bearing	Ball Bearing
Overall Height(mm)	128
Swivel Radius(mm)	90
Swivel Radius TL(mm)	120
Top Plate(mm)	105 x 85
Bolt Hole Centers	80 x 60
Non Marking	Yes
Heat Resistant	Yes
Noise Reduction	Yes

