











# BDS Series Castors with SEB Series Elastic Rubber Wheels

Muvtons - Black Elastic Rubber tyred wheels firmly chemically boned to precision machined cast iron cores. Highly resilient  $75^{\circ} \pm 5^{\circ}$  Shore A rubber provides very smooth and silent running. Can be used for power towing applications by suitably de-rating the load capacity. Wheel Bearing Options : Sealed precision ball bearings or roller bearings. Temperature range :  $-20^{\circ}\text{C}$  to  $\pm 75^{\circ}\text{C}$ . Tread Options : Anti-static; conductive and oil resistant wheels



Part No. Swivel Castor	Part No. Swivel With Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (Kgs)
									
BDS-415S-SEB	BDS-415-SEB-TL	BDS-415R-SEB	100 x 40	128	90	105 x 85	80 x 60	8	150
BDS-515S-SEB	BDS-515-SEB-TL	BDS-515R-SEB	125 x 40	155	105				200
BDS-62S-SEB	BDS-62-SEB-TL	BDS-62R-SEB	150 x 50	190	130				350
BDS-82S-SEB	BDS-82-SEB-TL	BDS-82R-SEB	200 x 50	238	160	135 x 110	105 x 75-80	10	450
BDS-102S-SEB	BDS-102-SEB-TL	BDS-102R-SEB	250 x 50	290	180				450