










BHS Series Castors with PNY Series Polyurethane Wheels

Liquid Cast High Quality Polyurethane chemically and mechanically locked to a strong polyamide core. Non-corrosive & non-marking, 95° shore A, non-staining, abrasion-resistant, floor-saving, low-noise operation, low rolling resistance Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings or roller bearings. Temperature range :-20°C to +85°C. Alternatively available with soft polyurethane tread



Part No. Swivel Castor	Part No. Swivel With Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (Kgs)
									
BHS-312S-PNY	BHS-312-PNY-TL	BHS-312R-PNY	80 x 30	105	78	105 x 85	82 x 62 slotted to 78 x 58	8	100
BHS-412S-PNY	BHS-412-PNY-TL	BHS-412R-PNY	100 x 35	128	88				200
BHS-512S-PNY	BHS-512-PNY-TL	BHS-512R-PNY	125 x 35	155	107				250
BHS-615S-PNY	BHS-615-PNY-TL	BHS-615R-PNY	150 x 40	190	135	135 X 110	110 x 85 slotted to 100 x 75	10	300
BHS-82S-PNY	BHS-82-PNY-TL	BHS-82R-PNY	200 x 50	235	155				350