









# BHS Series Castors with SJS Series Polyurethane Wheels

Muvtons medium duty Polyurethane wheels  $93^{\circ} \pm 3^{\circ}$  Shore A for medium duty applications offer a cost effective yet a good solution. Polyurethane tread is firmly bonded to precision machined cast iron cores offer smooth & noiseless running, are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings or roller bearings. Colour. Light Brown. Temperature range :  $-20^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ .



Part No. Swivel Castor	Part No. Swivel With Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (Kgs)
									
BHS-312S-SJS	BHS-312-SJS-TL	BHS-312R-SJS	80 x 30	105	78	105 x 85	82 x 62 slotted to 78 x 58	8	125
BHS-412S-SJS	BHS-412-SJS-TL	BHS-412R-SJS	100 x 35	128	88				225
BHS-512S-SJS	BHS-512-SJS-TL	BHS-512R-SJS	125 x 35	155	107				300
BHS-615S-SJS	BHS-615-SJS-TL	BHS-615R-SJS	150 x 40	190	135	135 X 110	110 x 85 slotted to 100 x 75	10	350
BHS-82S-SJS	BHS-82-SJS-TL	BHS-82R-SJS	200 x 50	235	155				350