



BHS-82-SJS-TL

Fork Properties

350Kgs. Load Capacity Medium Duty Castors

- Heavy duty pressed steel brackets
- Swivel brackets with double ball bearing raceways, dynamically pressed ensure low swivel headplay and long service life
- Kingpinless swivel head design in larger wheel diameters eliminates chances of kingpin failure
- Finish : Zinc Plated
- Options : Total lock brake system

Wheel Properties

Muvtons medium duty polyurethane treaded wheels 93° ±3C Shore A for medium and light applications offer a cost effective yet a good solution Polyurethane treads is firmly bonded to precision machined and floor protective. Tested & Guaranteed against bond failures. Wheel bearing options: Sealed precision ball bearings, tapered roller bearings or roller bearings. Color: Light Brown, Temperature Range : -20°C to +85°C.

Technical Data

Castor Type	Swivel Castor with Brake
Wheel Material	Polyurethane
Wheel Hardness	93° ± 3° Shore A
Wheel Center	Cast Iron
Wheel Dia(mm)	200
Tread Width(mm)	50
Load Capacity(kg)	350
Wheel Bearing	Ball Bearing
Overall Height(mm)	235
Swivel Radius(mm)	155
Swivel Radius TL(mm)	168
Top Plate(mm)	135 x 110
Bolt Hole Centers	110 x 85 to 100 x 75
Non Marking	Yes
Heat Resistant	Yes
Noise Reduction	Yes

