


BHS Series Castors with NY Series Nylon Wheels

Injection Moulded from high quality polyamide offer high abrasion resistance, low rolling resistance & smooth running on even floors. Corrosion resistant, provide chemical resistance to alcohol, salts, grease and some acids in mild concentration. Not recommended for epoxy coated floor surfaces. Wheel Bearing Options :Sealed precision ball bearings or roller bearings. Colour : Natural White Temperature range :- 40°C to +80°C.



Part No. Swivel Castor	Part No. Swivel With Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (Kgs)
									
BHS-312S-NY	BHS-312-NY-TL	BHS-312R-NY	80 x 30	105	78	105 x 85	82 x 62 slotted to 78 x 58	8	150
BHS-412S-NY	BHS-412-NY-TL	BHS-412R-NY	100 x 35	128	88				250
BHS-512S-NY	BHS-512-NY-TL	BHS-512R-NY	125 x 35	155	107				300
BHS-615S-NY	BHS-615-NY-TL	BHS-615R-NY	150 x 40	190	135	135 X 110	110 x 85 slotted to 100 x 75	10	350
BHS-82S-NY	BHS-82-NY-TL	BHS-82R-NY	200 x 50	235	155				350