



BHS-82S-NY

Fork Properties

350Kgs. Load Capacity Medium Duty Castors

- Heavy duty pressed steel brackets
- Swivel brackets with double ball bearing raceways, dynamically pressed ensure low swivel headplay and long service life
- Kingpinless swivel head design in larger wheel diameters eliminates chances of kingpin failure
- Finish : Zinc Plated
- Options : Total lock brake system

Wheel Properties

Injection Moduled high quality polyamide offer high abrasion resistance, low rolling resistance & smooth running on even floors. Corrosion resistant, provide chemical resistance to alcohol, grease and some acids in mild concentration. Not recommended for epoxy coated floor surfaces. Wheel Bearing Options: Sealed Precision ball bearings or roller bearings. Color:Natural White Temperature range:-40°C to +80°C.

Technical Data

| | |
|--------------------|-----------------------------|
| Castor Type | Swivel Castor without Brake |
| Wheel Material | Nylon Polyamide |
| Wheel Center | Nylon Polyamide |
| Wheel Dia(mm) | 200 |
| Tread Width(mm) | 50 |
| Load Capacity(kg) | 350 |
| Wheel Bearing | Ball Bearing |
| Overall Height(mm) | 235 |
| Swivel Radius(mm) | 155 |
| Top Plate(mm) | 135 x 110 |
| Bolt Hole Centers | 110 x 85 to 100 x 75 |
| Non Marking | No |
| Heat Resistant | Yes |
| Noise Reduction | - |

