



BHS Series Castors with RNY Series Elastic Rubber Wheels

Muvtons - black Elastic Rubber tyred wheels firmly boned to heavy duty polyamide core. Highly resilient $75^{\circ} \pm 5^{\circ}$ Shore A rubber provides very smooth and silent running. Wheel Bearing Options : Sealed precision ball bearings, tapered or roller bearings. Temperature range : -20°C to $\pm 75^{\circ}\text{C}$. Tread Options : Anti-static; conductive and oil resistant rubber.



Part No. Swivel Castor	Part No. Swivel With Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (Kgs)
									
BHS-312S-RNY	BHS-312-RNY-TL	BHS-312R-RNY	80 x 30	105	78	105 x 85	82 x 62 slotted to 78 x 58	8	100
BHS-412S-RNY	BHS-412-RNY-TL	BHS-412R-RNY	100 x 35	128	88				125
BHS-512S-RNY	BHS-512-RNY-TL	BHS-512R-RNY	125 x 35	155	107				150
BHS-615S-RNY	BHS-615-RNY-TL	BHS-615R-RNY	150 x 40	190	135	135 X 110	110 x 85 slotted to 100 x 75	10	200
BHS-82S-RNY	BHS-82-RNY-TL	BHS-82R-RNY	200 x 50	235	155				300