












GGSE Castors with SAS Series Polyurethane Wheels

Muvtons Premium Polyurethane treaded wheels $93^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running, are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range : -20° C to $+85^{\circ}$ C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GGSE-42S-SAS	GGSE-42S-SAS-TL	GGSE-42R-SAS	100 x 50	143	85	105	138 x 110	105 x 75-80	10	400
GGSE-52S-SAS	GGSE-52S-SAS-TL	GGSE-52R-SAS	125 x 50	165	101	110				550
GGSE-62S-SAS	GGSE-62S-SAS-TL	GGSE-62R-SAS	150 x 50	190	120	140				600
GGSE-82S-SAS	GGSE-82S-SAS-TL	GGSE-82R-SAS	200 x 50	241	156	163				600
GGSE-102S-SAS	GGSE-102S-SAS-TL	GGSE-102R-SAS	250 x 50	295	194	195				600