












# GGSE Castors with ME Series Ergonomic Wheels

Muvtons Ergonomic Wheels for effortless rolling, very low push-pull efforts required to move heavy loads. Generous amount of premium Polyurethane 93° ±3° Shore A, firmly bonded, mechanically & chemically, to precision machined cores. Proven for excellent performance in most demanding applications for manual and power towing. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Softer 83° ±3° Shore A Durometer for greater tractive resistance and harder 73° ±3° Shore D polyurethane treads for extremely low rolling resistance are also offered. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GGSE-42S-ME	GGSE-42S-ME-TL	GGSE-42R-ME	100 x 50	143	85	105	138 x 110	105 x 75-80	10	350
GGSE-52S-ME	GGSE-52S-ME-TL	GGSE-52R-ME	125 x 50	165	101	110				450
GGSE-62S-ME	GGSE-62S-ME-TL	GGSE-62R-ME	150 x 50	190	120	140				575
GGSE-82S-ME	GGSE-82S-ME-TL	GGSE-82R-ME	200 x 50	241	156	163				600