












GGSE Castors with SJS Series Polyurethane Wheels

Muvtons medium duty Polyurethane treaded wheels $93^{\circ} \pm 3^{\circ}$ Shore A for medium and light applications offer a cost-effective yet a good solution. Polyurethane tread is firmly bonded to precision machined cast iron cores offer smooth & noiseless running, are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range : -20°C to $+85^{\circ} \text{C}$.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GGSE-42S-SJS	GGSE-42S-SJS-TL	GGSE-42R-SJS	100 x 50	143	85	105	138 x 110	105 x 75-80	10	325
GGSE-52S-SJS	GGSE-52S-SJS-TL	GGSE-52R-SJS	125 x 50	165	101	110				450
GGSE-62S-SJS	GGSE-62S-SJS-TL	GGSE-62R-SJS	150 x 50	190	120	140				550
GGSE-82S-SJS	GGSE-82S-SJS-TL	GGSE-82R-SJS	200 x 50	241	156	163				600