


# SAB Forged Precision Bearing Castors with SZS Series Soft Polyurethane Wheels

Muvtons Premium Soft Durometer Polyurethane treaded wheels 83° ±3° Shore A, firmly bonded to precision machined cast iron cores. These wheels have been designed in response to noise problems and allow loads to be cushioned. The use of 'lively' polyurethane materials allows these wheels to 'flex & roll' over debris and obstacles without picking up objects. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
SAB-42S-SZS	SAB-42S-SZS-TL	GRDDE-42R-SZS	100 x 50	150	95	95	138 x 110	105 x 75-80	10	250
SAB-52S-SZS	SAB-52S-SZS-TL	GRDDE-52R-SZS	125 x 50	175	120	110				350
SAB-62S-SZS	SAB-62S-SZS-TL	GRDDE-62R-SZS	150 x 50	200	130	135				450
SAB-82S-SZS	SAB-82S-SZS-TL	GRDDE-82R-SZS	200 x 50	250	155	160				650
SAB-102S-SZS	SAB-102S-SZS-TL	GRDDE-102R-SZS	250 x 50	300	198	195				750