



ABLP-103R-SAS

Fork Properties

2000kgs, Load capacity Forged Precision Bearing Castors

- Single piece forged alloy steel top plate with an integrally forged kingpin & forged fork base.
- Combination of Precision thrust bearing and tapered roller bearing in the swivel head
- Totally sealed swivel head with grease nipple
- Slotted nut and cotter pin arrangement allow adjustment of swivel head play during usage
- 10 mm thick formed legs robotically welded inside & outside to 90 mm fork spacing
- 20 mm wheel axle
- Finish : Zinc Plated ; ROHS Compliant or Black polymer colour coted
- Options : 4 way Directional Lock, Total Lock, Wheel Face Brake

Wheel Properties

Muvtons premium polyurethane treaded wheels $93^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & guaranteed against bond failures. Wheel bearing options : Sealed precision ball bearings, tapered roller bearings or roller bearings, color, light brown. Temperature range : -20°C to +85°C. Tread options: Anti static : Conductive wheels are available.

Technical Data

| | |
|--------------------|------------------------------------|
| Castor Type | Rigid Castor without Brake |
| Wheel Material | Polyurethane |
| Wheel Hardness | $93^{\circ} \pm 3^{\circ}$ Shore A |
| Wheel Center | Cast Iron |
| Wheel Dia(mm) | 250 |
| Tread Width(mm) | 75 |
| Load Capacity(kg) | 1800 |
| Wheel Bearing | Ball Bearing |
| Overall Height(mm) | 314 |
| Top Plate(mm) | 175 x 140 |
| Bolt Hole Centers | 140 x 105 |
| Non Marking | yes |
| Heat Resistant | Yes |
| Noise Reduction | yes |

