












ABLP Forged Precision Bearing Castors with SAS Series Polyurethane Wheels

Muvtons Premium Polyurethane treaded wheels $93^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running, are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range : -20°C to $+85^{\circ} \text{C}$. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
ABLP-63S-SAS	ABLP-63S-SAS-TL	ABLP-63R-SAS	150 x 75	212	130	140	175 x 140	140 x 105	12	1050
ABLP-83S-SAS	ABLP-83S-SAS-TL	ABLP-83R-SAS	200 x 75	264	167	167				1400
ABLP-103S-SAS	ABLP-103S-SAS-TL	ABLP-103R-SAS	250 x 75	314	205	205				1800
ABLP-123S-SAS	ABLP-123S-SAS-TL	ABLP-123R-SAS	300 x 75	365	232	232				2000