












ABE75 Forged Precision Bearing Castors with SAS Series Polyurethane Wheels

Muvtons Premium Polyurethane treaded wheels $93^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running, are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range : -20°C to $+85^{\circ} \text{C}$. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
ABE75-84S-SAS	ABE75-84S-SAS-WFB	ABE75-84R-SAS	200 x 100	280	165	325	255 x 200	210 x 160	16	1800
ABE75-104S-SAS	ABE75-104S-SAS-WFB	ABE75-104R-SAS	250 x 100	330	195	355				2200
ABE75-124S-SAS	ABE75-124S-SAS-WFB	ABE75-124R-SAS	300 x 100	395	235	395				2800
ABE75-164S-SAS	ABE75-164S-SAS-WFB	ABE75-164R-SAS	400 x 100	495	300	445				3500