



DABE75-104S-SAS-WFB

Fork Properties

7500kgs load capacity forged precision bearing castors

- ▶ Single piece forged alloy steel top plate with an integrally forged kingpin & forged fork base
- ▶ Combination of precision thrust bearing and tapered roller bearing in the swivel head
- ▶ Totally sealed swivel head with grease nipple
- ▶ Slotted Nut and Cotter pin arrangement allow adjustment of swivel head play during usage
- ▶ 12 mm thick formed legs robotically welded inside & outside to 114mm x 2 fork spacing
- ▶ 30mm wheel axle
- ▶ Finish : Zinc Plated, ROHS compliant or black polymer color coated
- ▶ Options : 4 way directional lock, Wheel face brake

Wheel Properties

Muvtons premium polyurethane treaded wheels 93° ±3° Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & guaranteed against bond failures. Wheel bearing options : Sealed precision ball bearings, tapered roller bearings or roller bearings, color, light brown. Temperature range : -20°C to +85°C. Tread options: Anti static : Conductive wheels are available.

Technical Data

Castor Type	Swivel Castor with Brake
Wheel Material	Polyurethane
Wheel Hardness	93° ± 3° Shore A
Wheel Center	Cast Iron
Wheel Dia(mm)	250
Tread Width(mm)	100 x 2
Load Capacity(kg)	4400
Wheel Bearing	Ball Bearing
Overall Height(mm)	330
Swivel Radius(mm)	375
Top Plate(mm)	255 x 200
Bolt Hole Centers	210 x 160
Non Marking	yes
Heat Resistant	Yes
Noise Reduction	yes

