










ABE50 Forged Precision Bearing Castors with SAS Series Polyurethane Wheels

Muvtons Premium Polyurethane treaded wheels $93^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running, are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range : -20° C to $+85^{\circ}$ C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
ABE50-63S-SAS	ABE50-63S-SAS-WFB	ABE50-63R-SAS	150 x 75	212	136	290	200 x 160	160 x 120	16	1050
ABE50-83S-SAS	ABE50-83S-SAS-WFB	ABE50-83R-SAS	200 x 75	264	165	325				1400
ABE50-103S-SAS	ABE50-103S-SAS-WFB	ABE50-103R-SAS	250 x 75	314	205	365				1800
ABE50-123S-SAS	ABE50-123S-SAS-WFB	ABE50-123R-SAS	300 x 75	375	230	385				2200
ABE50-163S-SAS	ABE50-163S-SAS-WFB	ABE50-163R-SAS	400 x 75	475	300	445				2500