



ABE50-63S-SZS-WFB

Fork Properties

5000kgs load capacity forged precision bearing castors

- Single piece forged alloy steel top plate with an integrally forged kingpin & forged fork base
- Combination of precision thrust bearing and tapered roller bearing in the swivel head
- Totally sealed swivel head with grease nipple
- Slotted Nut and Cotter pin arrangement allow adjustment of swivel head play during usage
- 10 mm thick formed legs robotically welded inside & outside to 90mm fork spacing
- 25mm wheel axle
- Finish : Zinc Plated, ROHS compliant or black polymer color coated
- Options : 4 way directional lock, Total lock, Wheel face brake

Wheel Properties

Muvtons premium soft durometer polyurethane threaded wheels $83^{\circ} \pm 3^{\circ}$ Shore A, Firmly bonded to precision machined cast iron cores. These wheels have been designed to response to noise problems and allow loaded to be cushioned. The use of lively polyurethane materials allows these wheels to flex & roll over debris and obstacles without picking up objects. They are non marking and floor protective. Tested & guaranteed against bond failures. Wheel bearing options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range; -20°C to $+85^{\circ}\text{C}$. Thread options : Anti static : conductive wheels are available.

Technical Data

Castor Type	Swivel Castor with Brake
Wheel Material	Polyurethane
Wheel Hardness	$83^{\circ} \pm 3^{\circ}$ Shore A
Wheel Center	Cast Iron
Wheel Dia(mm)	150
Tread Width(mm)	75
Load Capacity(kg)	800
Wheel Bearing	Ball Bearing
Overall Height(mm)	212
Swivel Radius(mm)	136
Swivel Radius WFB(mm)	290
Top Plate(mm)	200 x 160
Bolt Hole Centers	160 x 120
Non Marking	Yes
Heat Resistant	Yes
Noise Reduction	Yes

