



## DABE50-103S-SAS

### Fork Properties

#### 5000kgs load capacity forged precision bearing castors

- Single piece forged alloy steel top plate with an integrally forged kingpin & forged fork base
- Combination of precision thrust bearing and tapered roller bearing in the swivel head
- Totally sealed swivel head with grease nipple
- Slotted Nut and Cotter pin arrangement allow adjustment of swivel head play during usage
- 10 mm thick formed legs robotically welded inside & outside to 90mm + 90mm fork spacing
- 25mm wheel axle
- Finish : Zinc Plated, ROHS compliant or black polymer color coated
- Options : 4 way directional lock, Wheel face brake

### Wheel Properties

Muvtons premium polyurethane threaded wheels 93° ±3° shore a, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & guaranteed against bond failures. Wheel bearing options : sealed precision ball bearings, tapered roller bearings or roller bearings, color, light brown. Temperature range : - 20°C to +85°C. Tread options: anti static : conductive wheels are available.

### Technical Data

Castor Type	Swivel Castor without Brake
Wheel Material	Polyurethane
Wheel Hardness	93° ± 3° Shore A
Wheel Center	Cast Iron
Wheel Dia(mm)	250
Tread Width(mm)	75x2
Load Capacity(kg)	3600
Wheel Bearing	Ball Bearing
Overall Height(mm)	314
Swivel Radius(mm)	220
Top Plate(mm)	200 x 160
Bolt Hole Centers	160 x 120
Non Marking	Yes
Heat Resistant	Yes
Noise Reduction	Yes

