












DABE50 Forged Twin Wheel Castors with MCNY Series Cast Polyamide Wheels

Muvtons MCNY Wheels produced from high impact resistant cast polyamide are the ultimate choice for extremely high loads where metallic wheels are not an option. These wheels possess very high abrasion resistance and offer low rolling resistance under extreme loads. Can be used in corrosive applications. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or plain bore. Temperature range : -30° C to +80° C.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABE50-63S-MCNY	DABE50-63S-MCNY-WFB	DABE50-63R-MCNY	150 x 80 x 2	212	160	310	200 x 60	160 x 120	16	5000
DABE50-83S-MCNY	DABE50-83S-MCNY-WFB	DABE50-83R-MCNY	200 x 80 x 2	264	190	350				5000
DABE50-103S-MCNY	DABE50-103S-MCNY-WFB	DABE50-103R-MCNY	250 x 80 x 2	314	220	375				5000
DABE50-123S-MCNY	DABE50-1232S-MCNY-WFB	DABE50-123R-MCNY	300 x 80 x 2	375	245	395				5000
DABE50-163S-MCNY	DABE50-163S-MCNY-WFB	DABE50-163R-MCNY	400 x 80 x 2	475	310	450				5000