









# GRDDE Twin Wheel Castors with SAS Series Polyurethane Wheels

Muvtons Premium Polyurethane treaded wheels  $93^{\circ} \pm 3^{\circ}$  Shore A, firmly bonded to precision machined cast iron cores offer low rolling resistance, smooth & noiseless running, are non-marking and floor protective. These wheels possess high abrasion & cut resistance and are resistant to tearing. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Colour: Light Brown. Temperature range :  $-20^{\circ} \text{C}$  to  $+85^{\circ} \text{C}$ . Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GRDDE-42S-SAS	GRDDE-42S-SAS-WFB	GRDDE-42R-SAS	100 x 50 x 2	150	125	250	150 x 110	105 x 80 Slotted to 121/59	12	800
GRDDE-52S-SAS	GRDDE-52S-SAS-WFB	GRDDE-52R-SAS	125 x 50 x 2	177	127	254				1100
GRDDE-62S-SAS	GRDDE-62S-SAS-WFB	GRDDE-62R-SAS	150 x 50 x 2	200	144	265				1500
GRDDE-82S-SAS	GRDDE-82S-SAS-WFB	GRDDE-82R-SAS	200 x 50 x 2	250	167	300				1500
GRDDE-102S-SAS	GRDDE-102S-SAS-WFB	GRDDE-102R-SAS	250 x 50 x 2	300	205	328				1500