

GRDDE Twin Wheel Castors with SZS Series Soft Polyurethane Wheels

Muvtons Premium Soft Durometer Polyurethane treaded wheels 83° ±3° Shore A, firmly bonded to precision machined cast iron cores. These wheels have been designed in response to noise problems and allow loads to be cushioned. The use of 'lively' polyurethane materials allows these wheels to 'flex & roll' over debris and obstacles without picking up objects. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
GRDDE-42S-SZS	GRDDE-42S-SZS-WFB	GRDDE-42R-SZS	100 x 50 x 2	150	125	250	150 x 110	105 x 80	12	500
GRDDE-52S-SZS	GRDDE-52S-SZS-WFB	GRDDE-52R-SZS	125 x 50 x 2	177	127	700				
GRDDE-62S-SZS	GRDDE-62S-SZS-WFB	GRDDE-62R-SZS	150 x 50 x 2	200	144	900				
GRDDE-82S-SZS	GRDDE-82S-SZS-WFB	GRDDE-82R-SZS	200 x 50 x 2	250	167	1300				
GRDDE-102S-SZS	GRDDE-102S-SZSS-WFB	GRDDE-102R-SZS	250 x 50 x 2	300	205	328				1500