












# GRDDE Twin Wheel Castors with SFS Series Solid Elastomer Wheels

Muvtons exclusively designed "Real Solid" Elastomer Wheels - produced from premium liquid cast polyurethane 73° ±3° Shore D mechanically & chemically locked to a non-corrosive metallic core that holds the wheel bearings and also provides structural rigidity under heavy loads. These wheels resist compression set, have excellent resilience for easy movement even under high loads and expel floor debris. Can be used for corrosive applications with suitable bearings. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor	Wheel Dia x Tread Width	Overall Height	Swivel Radius	Swivel Radius with WFB	Top Plate	Bolt Hole Centers	Attaching Bolt Size	Load Cap. (kgs).
										
GRDDE-42S-SFS	GRDDE-42S-SFS-WFB	GRDDE-42R-SFS	100 x 50 x 2	150	125	250	150 x 110	105 x 80 Slotted to 121/59	10	750
GRDDE-52S-SFS	GRDDE-52S-SFS-WFB	GRDDE-52R-SFS	125 x 50 x 2	177	127	254				1000
GRDDE-62S-SFS	GRDDE-62S-SFS-WFB	GRDDE-62R-SFS	150 x 50 x 2	200	144	265				1350
GRDDE-82S-SFS	GRDDE-82S-SFS-WFB	GRDDE-82R-SFS	200 x 50 x 2	250	167	300				1500