












GRDDE Twin Wheel Castors with SEB Series Elastic Rubber Wheels

Muvtons - black Elastic Rubber tyred wheels firmly chemically bonded to precision machined cast iron cores. Highly resilient $75^{\circ} \pm 5^{\circ}$ Shore A rubber provides very smooth and silent running. Can be used for power towing applications by suitably de-rating the load capacity. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20°C to $+75^{\circ} \text{C}$. Tread Options : Anti-static; conductive and oil resistant wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GRDDE-42S-SEB	GRDDE-42S-SEB-WFB	GRDDE-42R-SEB	100 x 50 x 2	150	125	250	150 x 110	105 x 80 Slotted to 121/59	12	420
GRDDE-52S-SEB	GRDDE-52S-SEB-WFB	GRDDE-52R-SEB	125 x 50 x 2	177	127	254				550
GRDDE-62S-SEB	GRDDE-62S-SEB-WFB	GRDDE-62R-SEB	150 x 50 x 2	200	144	265				700
GRDDE-82S-SEB	GRDDE-82S-SEB-WFB	GRDDE-82R-SEB	200 x 50 x 2	250	167	300				900
GRDDE-102S-SEB	GRDDE-102S-SEB-WFB	GRDDE-102R-SEB	250 x 50 x 2	300	205	328				1000