



## GRDE-52S-DF-TL

### Fork Properties

#### 1500 Kgs. Load Capacity Forged Kingpinless Castors

- Single piece forged alloy steel top plate & fork base
- Induction hardened raceways ensure swivel head longevity
- Totally sealed swivel head with grease nipple
- 6mm thick cylindrically formed legs robotically welded inside & outside to 65mm fork spacing
- 12mm Wheel Axle
- Finish : Zinc Plated, ROHS compliant or black polymer color coated
- Options : 4 way directional lock, Total lock, Wheel face brake

### Wheel Properties

Muvtons drop forged wheels are hot forged from alloy steels and can be used in the roughest of applications on the poorest of floors. These are virtually in-destructible within their capacity range. Tread faces are fully machined for easy maneuverability - these wheels offer high abrasion and oil resistance. Wheel bearing options: sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range:-100° c to +600° c.

### Technical Data

Castor Type	Swivel Castor with Brake
Wheel Material	Alloy Steel
Wheel Dia(mm)	125
Tread Width(mm)	50
Load Capacity(kg)	1000
Wheel Bearing	Ball Bearing
Overall Height(mm)	177
Swivel Radius(mm)	115
Swivel Radius TL(mm)	115
Top Plate(mm)	150 x 110
Bolt Hole Centers	105 x 80 to 121/59
Non Marking	-
Heat Resistant	Yes
Noise Reduction	-

