












# DABLP Forged Twin Wheel Castors with SEB Series Elastic Rubber Tyred Wheels

Muvtons - black Elastic Rubber tyred wheels firmly chemically bonded to precision machined cast iron cores. Highly resilient  $75^{\circ} \pm 5^{\circ}$  Shore A rubber provides very smooth and silent running. Can be used for power towing applications by suitably de-rating the load capacity. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range :  $-20^{\circ} \text{C}$  to  $+75^{\circ} \text{C}$ . Tread Options : Anti-static; conductive and oil resistant wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABLP-522S-SEB	DABLP-522S-SEB-WFB	DABLP-522R-SEB	125 x 50 x 2	185	120	245	175 x 140	140 x 105	12	550
DABLP-622S-SEB	DABLP-622S-SEB-WFB	DABLP-622R-SEB	150 x 50 x 2	212	140	265				700
DABLP-822S-SEB	DABLP-822S-SEB-WFB	DABLP-822R-SEB	200 x 50 x 2	264	175	303				900
DABLP-1022S-SEB	DABLP-1022S-SEB-WFB	DABLP-1022R-SEB	250 x 50 x 2	314	212	340				1000
DABLP-1222S-SEB	DABLP-1222S-SEB-WFB	DABLP-1222R-SEB	300 x 50 x 2	365	240	368				1300