












DABLP Forged Twin Wheel Castors with DF Series Drop Forged Steel Wheels

Muvtons Drop Forged Wheels are hot forged from Alloy Steels and can be used in the roughest of applications on the poorest of floors. These are virtually in-destructible within their capacity range. Tread faces are fully machined for easy maneuverability - these wheels offer high abrasion and oil resistance. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -100° C to +600° C.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABLP-522S-DF	DABLP-522S-DF-WFB	DABLP-522R-DF	125 x 50 x 2	185	120	245	175 x 140	140 x 105	12	2000
DABLP-622S-DF	DABLP-622S-DF-WFB	DABLP-622R-DF	150 x 50 x 2	212	140	265				2000
DABLP-822S-DF	DABLP-822S-DF-WFB	DABLP-822R-DF	200 x 50 x 2	264	175	303				2000
DABLP-1022S-DF	DABLP-1022S-DF-WFB	DABLP-1022R-DF	250 x 50 x 2	314	212	340				2000