






ABE75 Forged Precision Bearing Castors with SFS Series Solid Elastomer Wheels

Muvtons exclusively designed "Real Solid" Elastomer Wheels - produced from premium liquid cast polyurethane 73° ±3° Shore D mechanically & chemically locked to a non-corrosive metallic core that holds the wheel bearings and also provides structural rigidity under heavy loads. These wheels resist compression set, have excellent resilience for easy movement even under high loads and expel floor debris. Can be used for corrosive applications with suitable bearings. They are non-marking and floor protective. Tested & Guaranteed against bond failures.

Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
ABE75-84S-SFS	ABE75-84S-SFS-WFB	ABE75-84R-SFS	200 x 100	280	165	325	255 x 200	210 x 160	16	1400
ABE75-104S-SFS	ABE75-104S-SFS-WFB	ABE75-104R-SFS	250 x 100	330	195	355				1900
ABE75-124S-SFS	ABE75-124S-SFS-WFB	ABE75-124R-SFS	300 x 100	395	235	395				2050