











SAB Forged Precision Bearing Castors with MCI Series Cast Iron Wheels

Muvtons special grey cast iron wheels - solid core construction, tread face fully machined and crown treaded for extremely easy maneuverability. These wheels offer high abrasion and oil resistance, can be used upto 600° C with appropriate wheel bearings. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -100° C to +600° C.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
SAB-42S-MCI	SAB-42S-MCI-TL	SAB-42R-MCI	100 x 50	150	95	95	138 x 110	105 x 75-80	10	450
SAB-52S-MCI	SAB-52S-MCI-TL	SAB-52R-MCI	125 x 50	175	120	110				550
SAB-62S-MCI	SAB-62S-MCI-TL	SAB-62R-MCI	150 x 50	200	130	135				800
SAB-82S-MCI	SAB-82S-MCI-TL	SAB-82R-MCI	200 x 50	250	155	160				1000
SAB-102S-MCI	SAB-102S-MCI-TL	SAB-102R-MCI	250 x 50	300	198	195				1500