



SAB-82S-DF-TL

Fork Properties

1500kgs load capacity forged precision bearing castors.

- Single piece forged alloy steel top plate with an integrally forged kingpin & forged fork base.
- Combination of Precision thrust bearing and tapered roller bearing in the swivel head
- Totally sealed swivel head with grease nipple
- Slotted nut and cotter pin arrangement allow adjustment of swivel head play during usage
- 6 mm thick cylindrical formed legs robotically welded inside & outside to 65 mm fork spacing
- 12 mm wheel axle
- Finish : Zinc Plated ; ROHS Compliant or Black polymer colour coted
- Options : 4 way directional lock, total lock, wheel face brake

Wheel Properties

Muvtons drop forged wheels are hot forged from alloy steels and can be used in the roughest of applications on the poorest of floors. These are virtually in-destructible within their capacity range . Tread faces are fully machined for easy maneuverability - these wheels offer high abrasion and oil resistance . Wheel bearing options: sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range:-100° c to +600° c.

Technical Data

Castor Type	Swivel Castor with Brake
Wheel Material	Alloy Steel
Wheel Dia(mm)	200
Tread Width(mm)	50
Load Capacity(kg)	1500
Wheel Bearing	Ball Bearing
Overall Height(mm)	250
Swivel Radius(mm)	155
Swivel Radius TL(mm)	160
Top Plate(mm)	138 x 110
Bolt Hole Dia(mm)	105 x 75-80
Non Marking	-
Heat Resistant	Yes
Noise Reduction	-

