

# ABLP Forged Precision Bearing Castors with SFS Series Solid Elastomer Wheels

Muvtons exclusively designed "Real Solid" Elastomer Wheels - produced from premium liquid cast polyurethane 73° ±3° Shore D mechanically & chemically locked to a non-corrosive metallic core that holds the wheel bearings and also provides structural rigidity under heavy loads. These wheels resist compression set, have excellent resilience for easy movement even under high loads and expel floor debris. Can be used for corrosive applications with suitable bearings. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
ABLP-63S-SFS	ABLP-63S-SFS-TL	ABLP-63R-SFS	150 x 75	212	130	140	175 x 140	140 x 105	12	1100
ABLP-83S-SFS	ABLP-83S-SFS-TL	ABLP-83R-SFS	200 x 75	264	167	167				1150
ABLP-103S-SFS	ABLP-103S-SFS-TL	ABLP-103R-SFS	250 x 75	314	205	205				1350
ABLP-123S-SFS	ABLP-123S-SFS-TL	ABLP-123R-SFS	300 x 75	365	232	232				1550