












ABLP Forged Precision Bearing Castors with SEB Series Elastic Rubber Tyred Wheels

Muvtons - black Elastic Rubber tyred wheels firmly chemically bonded to precision machined cast iron cores. Highly resilient $75^{\circ} \pm 5^{\circ}$ Shore A rubber provides very smooth and silent running. Can be used for power towing applications by suitably de-rating the load capacity. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20°C to $+75^{\circ} \text{C}$. Tread Options : Anti-static; conductive and oil resistant wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
ABLP-63S-SEB	ABLP-63S-SEB-TL	ABLP-63R-SEB	150 x 75	212	130	140	175 x 140	140 x 105	12	425
ABLP-83S-SEB	ABLP-83S-SEB-TL	ABLP-83R-SEB	200 x 75	264	167	167				550
ABLP-103S-SEB	ABLP-103S-SEB-TL	ABLP-103R-SEB	250 x 75	314	205	205				750
ABLP-123S-SEB	ABLP-123S-SEB-TL	ABLP-123R-SEB	300 x 75	365	232	232				850