












# DABE75 Forged Twin Wheel Castors with SFS Series Solid Elastomer Wheels

Muvtons exclusively designed "Real Solid" Elastomer Wheels - produced from premium liquid cast polyurethane 73° ±3° Shore D mechanically & chemically locked to a non-corrosive metallic core that holds the wheel bearings and also provides structural rigidity under heavy loads. These wheels resist compression set, have excellent resilience for easy movement even under high loads and expel floor debris. Can be used for corrosive applications with suitable bearings. They are non-marking and floor protective. Tested & Guaranteed against bond failures.

Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to +85° C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABE75-84S-SFS	DABE75-84S-SFS-WFB	DABE75-84R-SFS	200 x 100 x 2	280	200	350	255 x 200	210 x 160	16	2800
DABE75-104S-SFS	DABE75-104S-SFS-WFB	DABE75-104R-SFS	250 x 100 x 2	330	226	375				3800
DABE75-124S-SFS	DABE75-124S-SFS-WFB	DABE75-124R-SFS	300 x 100 x 2	395	261	420				4100