












DABE75 Forged Twin Wheel Castors with DF Series Drop Forged Steel Wheels

Muvtons Drop Forged Wheels are hot forged from Alloy Steels and can be used in the roughest of applications on the poorest of floors. These are virtually in-destructible within their capacity range. Tread faces are fully machined for easy maneuverability - these wheels offer high abrasion and oil resistance. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings.

Temperature range : -100° C to +600° C.



Part No. Swivel Castor	Part No. Swivel with Wheel Brake	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with WFB (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
DABE75-63S-DF	DABE75-63S-DF-WFB	DABE75-63R-DF	150 x 75 x 2	230	160	300	255 x 200	210 x 160	16	6000
DABE75-83S-DF	DABE75-83S-DF-WFB	DABE75-83R-DF	200 x 75 x 2	280	200	350				7000
DABE75-103S-DF	DABE75-103S-DF-WFB	DABE75-103R-DF	250 x 75 x 2	330	226	375				7500