



GGSE-52R-SFS

Fork Properties

600kgs, Load capacity Forged Kingpin type Castors

- Single Piece forged alloy steel top plate with integrally forged kingpin
- Sealed double ball raceways precision CNC machined
- Induction Hardened raceways ensure longevity of the castor
- Forged lower raceway
- 6mm thick formed legs robotically welded inside & outside
- 12mm wheel axle
- Finish : Zinc plated; ROHS compliant or black polymer color coated
- Option : 4 way directional lock , Total lock, Wheel face brake

Wheel Properties

Muvtons exclusively designed " Real Solid " Elastomer Wheels produced from premium liquid cast polyurethane 73° ±3° shore d mechanically & chemically locked to a non corrosive metallic core that holds the wheel bearings and also provides structural rigidity under heavy loads. These wheels resist compression set, have excellent resilience for easy movement even under high loads and expel floor debris. Can be used for corrosive applications with suitable bearings. They are non marking and floor protective. Tested & guaranteed against bond failures. Wheel bearing options : sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20°c to +85°c. Tread options:anti-static;conductive wheels are available.

Technical Data

| | |
|--------------------|----------------------------|
| Castor Type | Rigid Castor without Brake |
| Wheel Material | Polyurethane |
| Wheel Hardness | 73° ± 3° Shore D |
| Wheel Center | Aluminium |
| Wheel Dia(mm) | 125 |
| Tread Width(mm) | 50 |
| Load Capacity(kg) | 500 |
| Wheel Bearing | Ball Bearing |
| Overall Height(mm) | 165 |
| Top Plate(mm) | 138 x 110 |
| Bolt Hole Dia(mm) | 105 x 75-80 |
| Non Marking | yes |
| Heat Resistant | Yes |
| Noise Reduction | - |

