



BHS-SS-82S-PNY Caster Wheels

Fork Properties

350Kgs. Load capacity Stainless Steel Castors

- ▢ Heavy Duty Pressed stainless steel brackets
- ▢ swivel brackets with double ball bearing raceways, dynamically pressed ensure low swivel head play and long service life
- ▢ Kingpinless swivel head design in larger wheel diameter eliminates chances of kingpin failure
- ▢ Finish : Polished Stainless Steel
- ▢ Options : Total lock Brake System

Liquid Cast Quality polyurethane chemically and mechanically to a strong polyamide core. Non-corrosive & non-marking 95° shore A, non-Staining, abrasion-resistant, floor-saving, low-noise operation, low rolling resistance tested & guaranteed against bond failures. Wheel Bearing Options: Sealed precision ball bearing or roller bearings. Temperature range:-20°C to +85°C. Alternatively available with soft polyurethane tread.

Technical Data

Castor Type	Swivel Castor without Brake
Wheel Material	Polyurethane
Wheel Hardness	95° Shore A
Wheel Center	Nylon Polyamide
Wheel Dia(mm)	200
Tread Width(mm)	50
Load Capacity(kg)	350
Wheel Bearing	Ball Bearing
Overall Height(mm)	235
Swivel Radius(mm)	155
Top Plate(mm)	135 x 110
Bolt Hole Centers	110 x 85 to 100 x 75
Castor Pdf File Name	-
AutoCAD File Name	-
Non Marking	Yes
Heat Resistant	Yes
Noise Reduction	Yes

