












GHKE Castors with ME Series Ergonomic Wheels

Muvtons Ergonomic Wheels for effortless rolling, very low push-pull efforts required to move heavy loads. Generous amount of premium Polyurethane $93^{\circ} \pm 3^{\circ}$ Shore A, firmly bonded, mechanically & chemically, to precision machined cores. Proven for excellent performance in most demanding applications for manual and power towing. They are non-marking and floor protective. Tested & Guaranteed against bond failures. Softer $83^{\circ} \pm 3^{\circ}$ Shore A Durometer for greater tractive resistance and harder $73^{\circ} \pm 3^{\circ}$ Shore D polyurethane treads for extremely low rolling resistance are also offered. Wheel Bearing Options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range : -20° C to $+85^{\circ}$ C. Tread Options : Anti-static ; conductive wheels are available.



Part No. Swivel Castor	Part No. Swivel with Total Lock	Part No. Rigid Castor (mm)	Wheel Dia x Tread Width (mm)	Overall Height (mm)	Swivel Radius (mm)	Swivel Radius with TL (mm)	Top Plate (mm)	Bolt Hole Centers (mm)	Attaching Bolt Size (mm)	Load Cap. (kgs).
										
GHKE-42S-ME	GHKE-42S-ME-TL	GHKE-42R-ME	100 x 50	140	77	90	138 x 110	105 x 75-80	10	350
GHKE-52S-ME	GHKE-52S-ME-TL	GHKE-52R-ME	125 x 50	165	95	110				450
GHKE-62S-ME	GHKE-62S-ME-TL	GHKE-62R-ME	150 x 50	195	115	140				575
GHKE-82S-ME	GHKE-82S-ME-TL	GHKE-82R-ME	200 x 50	245	152	163				775
GHKE-102S-ME	GHKE-102S-ME-TL	GHKE-102R-ME	250 x 50	295	190	197				850