



## GHKE-52S-SZS-TL

### Fork Properties

#### 900 Kgs. Load Capacity Forged Kingpinless Castors

- Single piece forged alloy steel top plate & fork base
- Precision CNC machined raceways
- Induction hardened raceways ensure swivel head longevity
- Totally sealed swivel head with grease nipple
- 6mm thick fabricated construction of forks robotically welded inside & outside to 65mm fork spacing
- 12mm Wheel Axle
- Finish: Zinc plate; ROHS compliant or Black polymer color coated
- Options : 4 way directional lock, Total lock, Wheel face break

### Wheel Properties

Muvtons premium soft durometer polyurethane treaded wheels 83° ±3° Shore A, Firmly bonded to precision machined cast iron cores. These wheels have been designed to response to noise problems and allow loaded to be cushioned. The use of lively polyurethane materials allows these wheels to flex & roll over debris and obstacles without picking up objects. They are non marking and floor protective. Tested & guaranteed against bond failures. Wheel bearing options : Sealed precision ball bearings, tapered roller bearings or roller bearings. Temperature range; -20°C to +85°C. Thread options : Anti static : conductive wheels are available.

### Technical Data

|                      |                          |
|----------------------|--------------------------|
| Castor Type          | Swivel Castor with Brake |
| Wheel Material       | Polyurethane             |
| Wheel Hardness       | 83° ± 3° Shore A         |
| Wheel Center         | Cast Iron                |
| Wheel Dia(mm)        | 125                      |
| Tread Width(mm)      | 50                       |
| Load Capacity(kg)    | 350                      |
| Wheel Bearing        | Ball Bearing             |
| Overall Height(mm)   | 165                      |
| Swivel Radius(mm)    | 95                       |
| Swivel Radius TL(mm) | 110                      |
| Top Plate(mm)        | 138 x 110                |
| Bolt Hole Dia(mm)    | 105 x 75-80              |
| Non Marking          | yes                      |
| Heat Resistant       | yes                      |

